The life of sound.

Miracord[™] 50 Turntable

Smooth vinyl precision.

ELAC's Miracord 50 Turntable is designed to deliver exceptional vinyl transcription, inspired by the iconic Miracord name from the Golden Age of Stereo, when turntables reigned supreme. The Miracord 50 is carefully engineered with a belt-drive motor and die-cast aluminum platter. A precision static-balanced, straight-tube tonearm with removable headshell features a factory-mounted MM phono cartridge. Designed with convenience in mind, the Miracord 50 is equipped with a built-in defeatable phono preamplifier, allowing you to add this turntable to any music system.



Miracord 50 Turntable

The warmth of analog sound.

The resurgence of vinyl has created a groundswell of enthusiasm among audiophiles and music enthusiasts who have never before enjoyed the thrill of spinning an LP! The Miracord 50 is the perfect choice for those building a new LP collection, or for rediscovering the magic of an existing record library.



MIRACORD 50 TURNTABLE FEATURES

Anti-resonant Chassis

Superior isolation is achieved with a chassis designed to minimize the sonic effects of vibration and feedback. A low-noise DC servo motor drives a die-cast, high-inertia aluminum platter with special record mat via a rubber belt, resulting in stable speed and minimal wow and flutter.

Precision Tonearm and Cartridge

The tonearm is a static-balance, straighttube design with precision bearings, builtin anti-skate adjustment and removable bayonet-style headshell. A premounted

moving-magnet cartridge takes all the guesswork out of setup and assures proper vertical tracking angle, tracking weight and azimuth adjustment right out of the box.

Built-in Phono Equalizer Amplifier

Unlike most turntables, the Miracord 50 comes complete with a built-in defeatable phono preamp for correct RIAA equalization. That means you can add LP playback without having to add a costly phono stage to line-level preamps or digital-only systems. Just plug it in, put on a record and enjoy rich LP sound!

Contemporary Finish

Styled to complement any interior, the Miracord 50 is available with a silver chassis and gloss-black plinth. A hinged, tinted dustcover is included.



MIRACORD 50 TURNTABLE SPECIFICATIONS

DC motor

TURNTABLE SECTION

· Drive System Motor

Selectable Speeds Motor Servo

Rotation Speed Variation

Wow and Flutter

Signal-to-Noise Ratio

Platter Diameter

Belt drive

331/3 and 45 rpm

Speed rotation and servo system

+/-1%

0.1%

-67 dB or higher (A-weighted) -60 dB or higher (unweighted)

Aluminum die-cast

12.0 in / 300 mm

CARTRIDGE SECTION

 Type Audio-Technica AT91 moving magnet Stylus Construction Bonded diamond

Mount

Half-inch 20 Hz to 20 kHz Frequency Response

>18 dB **Channel Separation** Channel Balance 2.5 dB Vertical Tracking Angle 20 degrees

Stylus Pressure 2.0 g +/-0.5 g Cartridge Weight 5.0 g +/-0.5 g

Headshell Weight 11.0 g (including screws, nuts and wires)

TONEARM SECTION

Type

· Effective Arm Length Stylus Pressure Range

Cartridge Weight Range Effective Arm Mass

Overhang

Offset Angle

Anti-Skating Adjustment

Main Bearing

Aluminum tube, static-balanced

8.8 in / 223.6 mm

0 to 4.0 g 3.5 to 6.0 g

27.4 g 18.6 mm

25 degrees Supported

Stainless steel

PHONO EQUALIZER AMPLIFIER

Type

 Phono Output · Line Output

· Phono/Line

Supported Load Impedance

Moving magnet (MM)

2.5 mV (1 kHz, 3.54 cm/sec)

140 mV (-17 dBV) Switchable

47 kΩ

CONNECTOR VOLTAGE POWER CONSUMPTION DIMENSIONS (WXHXD) WEIGHT

RCA pin jack including RCA cable accessories 100 to 240 V AC / 50 to 60 Hz

1.5 W (less than 0.5 W at standby)

12.10 lb

5.5 x 16.05 x 14.20



