


# T2

THE PERFORMANCE  
SWEET SPOT



ALL-NEW  
CHASSIS

DUAL DAC  
ES9028PRO

DSD512  
22.6MHZ

PCM  
384KHZ

USB  
OUTPUT

INTERNAL  
POWER SUPPLY

# LUMIN

# T2

# LUMIN

ALL-NEW CHASSIS DESIGN  
FEATURING THICK CNC  
PANELS AND AN INTERNAL  
POWER SUPPLY

NEW GENERATION  
PROCESSOR

DUAL ES9028PRO SABRE DAC  
FEATURING DUAL-MONO  
OPERATION

DSD512 22.6MHz  
PCM 44.1-384kHz 16-32-bit

USB DIGITAL AUDIO OUTPUT

PCM & DSD UPSAMPLING

PRECISION 32-BIT INTERNAL  
DIGITAL VOLUME

COMPLETELY REDESIGNED  
ANALOGUE BUFFER WITH X1  
TECHNOLOGY



**STREAMING PROTOCOL:**

UPnP AV protocol with audio streaming extension (OpenHome). Roon Ready. Spotify Connect. Apple AirPlay. Songcast. Gapless Playback. On-Device Playlist

**SUPPORTED AUDIO FILE FORMATS:**

DSD:  
DSF (DSD), DFF (DSD), DoP (DSD)  
PCM:  
FLAC, Apple Lossless (ALAC), WAV, AIFF  
OTHER:  
MQA, MP3, AAC (in M4A container)

**SUPPORTED SAMPLE RATES & BIT DEPTHS:**

PCM, 44.1kHz-384kHz, 16-32-bit, Stereo  
DSD512, 22.6MHz, 1-bit, Stereo

**UPSAMPLING RATES & BIT DEPTHS:**

PCM 384kHz and DSD128 upsampling option for all files up to 192kHz

**SUPPORTED CONTROL DEVICES:**

Apple iOS devices. iOS 8.0 or later required  
Android devices. Android 4.0 (Ice Cream Sandwich) or later required

**APP FEATURES:**

Native support for TIDAL, MQA, Qobuz and TuneIn Radio. Tidal MQA and Qobuz high-res icons to identify high-res music. Multi-room simultaneous playback. Volume control. High-resolution artwork. Artwork caching. Search. Multiple tag handling. Composer tag support. Album-grouping in playlist. Automatic internet links to artists/album/songs. Saving, syncing and restoring of playlists (including Tidal and Qobuz)

**INPUT:**

Gigabit Ethernet Network (1000BASE-T) RJ45  
USB storage, flash drive, USB hard disk (Single-partition FAT32, NTFS, exFAT and EXT2/3)

**ANALOGUE AUDIO OUTPUT:**

XLR balanced, 6Vrms, pin 2 Hot  
RCA unbalanced, 3Vrms

**DIGITAL AUDIO OUTPUT:**

USB:  
DSD64-512 2.8-22.6MHz, 1-bit Stereo  
PCM 44.1-384kHz, 16-32-bit Stereo  
COAXIAL BNC:  
PCM 44.1kHz-192kHz, 16-24-bit  
DSD (DoP, DSD over PCM) 2.8MHz, 1-bit

**FINISH:**

Raw brushed aluminium  
Black anodised brushed aluminium

**POWER SUPPLY:**

Internal shielded 100-240V AC auto-ranging

**OTHER:**

Firmware-upgradable for further features and enhancements

LUMIN: 350mm (W), 350mm (D),  
60mm (H), 6kg

WWW.LUMINMUSIC.COM